

AC200MAX Portable Power Station



Specifications

	Area	JP	US	EU/AU/UK
Model	Battery Capacity	2048Wh		
	Cell Type	LiFePO4		
	Net Weight	28.1kg/61.9lbs		
	Dimensions (L*W*H)	420*280*386.5mm/16.5*11.0*15.2in		
	Charging Temperature	0°C~40°C/32°F~104°F		
	Discharging Temperature	-20°C~40°C/-4°F~104°F		
	Standard Battery Voltage	51.2VDC		
	Working Humidity	10%~90%		
AC Output	Power	2000W	2200W	
	Surge Power	4800W		
	Voltage	100VAC	120VAC	230VAC
	Current	20A	18.3A	9.6A
	Frequency	50Hz/60Hz		
	Inverter Efficiency	88%		
DC Output	Cigarette Lighter Port*1	12VDC/10A		
	USB-A*4	5V/3A*2 5-12VDC/3A,18W*2		
	USB-C*1	5V-15V/3A,20V/5A		
	DC5521*2	12VDC/10A		
	RV *1	12VDC/30A		
	Wireless Charging*2	5W/7.5W/10W/15W		
Input	AC Charging	500W Max.		
	Solar Charging	10~145V 900W Max		
	Car Charging	12/24V 8A		
	Solar+AC Charging	1,400W Max.		
Solar Input	Power	900W		
	Over-voltage Protection	145VDC		
	MPPT Voltage Range	10-145VDC		
	Current	15A		
	MPPT Quantity	1/1		
	T500 Adapter charging (On PV input port)	500W,8A		
	Car Charging	11.5-14.5V,8A		
T500 AC Adapter	Input Voltage	100-240VAC		
	Voltage Range	58.8V		
	Max. Charging Power	500W		

Scalability



External Battery Connection	External Battery	B230	B300
	Capacity	2048Wh	3072Wh
	Maxium Parrallable Battery Units	2	2
	Scalable Capacity	6144Wh	8192Wh